

IN THE CLAIMS

What is claimed is:

1 **1.** A dynamic server directory system, comprising:

2 at least one relational table that includes a plurality of entries that can
3 each store location data, status data, and feature data of server processes in a
4 distributed computing system that services client requests; and

5 an interface that may provide at least one entry from the at least one
6 relational table to a client.

1 **2.** The dynamic server directory system of claim 1, wherein:

2 the location data of an entry may comprise a network address; and

3 the entry may include a server name to identify a specific server at the
4 network address.

1 **3.** The dynamic server directory system of claim 1, further including:

2 a route table that can indicate at least one communication route to a
3 server host and the status of said route.

1 **4.** The dynamic server directory system of claim 1, further including:

2 a plurality of dynamic server directory agents that reside on different
3 host machines than the dynamic server directory, each dynamic server directory agent
4 caching at least a portion of the at least one relational table.

4 relational table that identifies a communication route corresponding to a given
5 host machine.

1 **9.** The dynamic server directory system of claim 8, further including:
2 the interface searches the server relational table and then the route
3 relational table to determine the route to a host machine for a given server
4 process.

1 **10.** The dynamic server directory system of claim 1, further including:
2 a plurality of dynamic server directory agents that reside on different
3 host machines than the dynamic server directory, each dynamic server
4 directory agent receiving periodic status communications from at least one
5 server process and notifying the dynamic server directory when status
6 communications fail; and
7 the dynamic server directory changes entries in the at least one
8 relational table in response to status communication failures.

1 **11.** The dynamic server directory of claim 10, further including:
2 a service master process that may subscribe with the DSD agent to be
3 notified of changes to the at least one relational table, the service master
4 performing at least one predetermined error response when the change to the
5 at least one relational table indicates a status communication failure has
6 occurred in a server process; and

7 the dynamic server directory forwards changes in the at least one
8 relational table to the DSD agent.

1 **12.** The dynamic server directory of claim 11, wherein:

2 the predetermined error response may be at least one response selected
3 from the group consisting of: attempting to restart the server process
4 corresponding to the failure, logging the failure error, notifying a system
5 administrator, generating a work order for the server process corresponding to
6 the error, activating another server process as a back-up to the server process
7 corresponding to the failure, shutting down a host machine for the server
8 process corresponding to the failure, and rebooting a host machine for the
9 server process corresponding to the failure.

1 **13.** The dynamic server directory of claim 1, wherein:

2 a plurality of client processes that may subscribe to be notified of changes to
3 the at least one relational table, a client process performing a resubmission of all
4 requests sent on a particular currently valid server route when the change to the at
5 least one relational table indicates a failure in the server process, or the route to the
6 server process.

1 **14.** A system, comprising:

2 a plurality of servers that may perform predetermined operations

3 according to requests from clients; and

4 a dynamic server directory that includes a plurality of relational tables,

5 each relational table storing feature information for the plurality of servers, the

6 feature information being accessible by a client to determine which server

7 may service a particular client request; and

8 a plurality of dynamic server directory agents that may perform

9 predetermined operations according to client subscriptions.

10

1 **15.** The system of claim 14, wherein:

2 the plurality of servers include storage servers that may access stored

3 files and metadata servers that may access metadata for the stored files.

1 **16.** The system of claim 14, wherein:

2 the dynamic server directory agent includes an interface that may

3 provide access to the relational tables in response to an action selected from

4 the group consisting of: the addition of a new entry to a relational table,

5 deletion of a entry from a relational table, search for a key, search for a server,

6 subscription to notification of changes in status, and maintenance of current

7 process information..

1 **17.** The system of claim 14, further including:

1 **20.** The method of claim 18, wherein:

2 selecting a server includes searching a first server information
3 relational table to determine a server route including a host machine on which
4 a desired server resides, and searching a second server information relational
5 table to determine a route to the host machine.

1 **21.** The method of claim 18, wherein:

2 the server information includes
3 at least one server relational table having entries that comprise
4 server identification, server route identification including host machine
5 identification, and a server status indication for each server process,
6 and
7 at least one route relational table having entries that comprise
8 host machine identification, route information, and host machine status
9 indication.

1 **22.** The method of claim 21, further including:

2 the plurality of servers includes a gateway servers that control access
3 to the distributed computing system, metadata servers that access metadata for
4 stored files, and storage servers that store files; and

5 the at least one server relational table includes a gateway server
6 relational table, a metadata server relational table, and a storage server
7 relational table.